



| ROPE DIA. (in) | RATED CAPACITY (tons) | | | MASTER LINK DIA. (in) | ALLOY HOOK WLL (tons) |
|-------------------|-----------------------|-----|-----|--------------------------|--------------------------|
| | 60° | 45° | 30° | | |
| 1/4 | 2.2 | 1.8 | 1.3 | 1/2 | 1 |
| 5/16 | 3.5 | 2.8 | 2 | 3/4 | 1 |
| 3/8 | 5 | 4.1 | 2.9 | 3/4 | 1-1/2 |
| 7/16 | 6.7 | 5.5 | 3.9 | 7/8 | 2 |
| 1/2 | 8.8 | 7.1 | 5.1 | 1 | 3 |
| 9/16 | 11 | 9 | 6.4 | 1 | 5 |
| 5/8 | 14 | 11 | 7.8 | 1-1/4 | 5 |
| 3/4 | 19 | 16 | 11 | 1-1/2 | 7 |
| 7/8 | 26 | 21 | 15 | 1-3/4 | 11 |
| 1 | 34 | 28 | 20 | 2 | 11 |
| 1-1/8 | 42 | 34 | 24 | 2-1/4 | 15 |
| 1-1/4 | 51 | 42 | 30 | 2-1/2 | 15 |
| 1-3/8 | 62 | 50 | 36 | 2-3/4 | 22 |
| 1-1/2 | 73 | 60 | 42 | 3-1/2 | 22 |

- Rated in US tons.
- If you don't see the configuration you're looking for on the site, fill out our online form or contact us for a quote.