

# Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

D0302046n

Declaration Date

10/31/2024

Tested Item #	84108SP0/ 84108TP0	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook
		8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook

### Additional Items Conforming Under this Declaration:

84106RP0	84106RP6	84106SP5	84106TP2	84107RP3X	84108RPOS	84108RP4	84108RP8S
84106RP1	84106SP0	84106SP6	84106TP3	84107SP3X	84108RP1	84108RP5	84108SP0
84106RP2	84106SP1	84106TP0	84106TP5	84107TP0	84108RP2	84108RP6	84108SP0S
84106RP3	84106SP2	84106TP0S	84106TP6	84107TP3X	84108RP3	84108RP8	84108SP1
84106RP5	84106SP3	84106TP1	84107RP0	84108RP0	84108RP3S	84108RP8D	84108SP2

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

**ANSI Z359.14-2021**

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

**Level 1:** FallTech Lab  
Outside the Scope of  
ISO/IEC Standard 17025:2017

**Level 2:** FallTech Lab  
Within the Scope of  
ISO/IEC Standard 17025:2017

**Level 3:** Independent 3rd Party Lab  
accredited to  
ISO/IEC Standard 17025:2017

Supporting  
Documentation

PC-2514

PC-2515

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

10/31/2024



International Accreditation Service, Inc  
3060 Saturn St, Ste 100  
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594  
ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

# Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

D0302046n

Declaration Date

10/31/2024

Tested Item #	84108SP0/ 84108TP0	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook
		8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook

### Additional Items Conforming Under this Declaration:

84108SP3	84108SP8	84108TP2	84108TP5	84109RP3	84109TP5
84108SP3S	84108SP8S	84108TP3	84108TP6	84109RP3S	FR84106RP3S
84108SP4	84108TP0	84108TP3S	84108TP8	84109RP5	FR84106TP3S
84108SP5	84108TP0S	84108TP3T	84108TP8D	84109TP3	
84108SP6	84108TP1	84108TP4	84108TP8S	84109TP3S	

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

**ANSI Z359.14-2021**

### Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

**Level 1:** FallTech Lab  
Outside the Scope of  
ISO/IEC Standard 17025:2017

**Level 2:** FallTech Lab  
Within the Scope of  
ISO/IEC Standard 17025:2017

**Level 3:** Independent 3rd Party Lab  
accredited to  
ISO/IEC Standard 17025:2017

Supporting  
Documentation

PC-2514


PC-2515

Authorized Signature

Name \_\_\_\_\_ Zachary Winters

Title \_\_\_\_\_ Engineering Manager

Date \_\_\_\_\_ 10/31/2024



FallTech Lab - TL-594  
ISO/IEC 17025:2017  
Alexander Andrew Inc dba FallTech

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	84108SP0 / 84108TP0		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

### Material/Sample Identification

Sample ID	Description
6274239	8' EdgeCore FT-X Class 2 LE SRL
6274196	8' EdgeCore FT-X Class 2 LE SRL
6274208	8' EdgeCore FT-X Class 2 LE SRL
6274201	8' EdgeCore FT-X Class 2 LE SRL
6274217	8' EdgeCore FT-X Class 2 LE SRL
6274199	8' EdgeCore FT-X Class 2 LE SRL
6274228	8' EdgeCore FT-X Class 2 LE SRL
6274203	8' EdgeCore FT-X Class 2 LE SRL
6274219	8' EdgeCore FT-X Class 2 LE SRL
6274235	8' EdgeCore FT-X Class 2 LE SRL
6274204	8' EdgeCore FT-X Class 2 LE SRL
6274188	8' EdgeCore FT-X Class 2 LE SRL
6274195	8' EdgeCore FT-X Class 2 LE SRL
6274216	8' EdgeCore FT-X Class 2 LE SRL
6274218	8' EdgeCore FT-X Class 2 LE SRL
6274233	8' EdgeCore FT-X Class 2 LE SRL
6274209	8' EdgeCore FT-X Class 2 LE SRL
6274207	8' EdgeCore FT-X Class 2 LE SRL
6274240	8' EdgeCore FT-X Class 2 LE SRL
6274191	8' EdgeCore FT-X Class 2 LE SRL
6274220	8' EdgeCore FT-X Class 2 LE SRL
6274230	8' EdgeCore FT-X Class 2 LE SRL
6274227	8' EdgeCore FT-X Class 2 LE SRL
6274212	8' EdgeCore FT-X Class 2 LE SRL
6274243	8' EdgeCore FT-X Class 2 LE SRL
6274197	8' EdgeCore FT-X Class 2 LE SRL
6274211	8' EdgeCore FT-X Class 2 LE SRL
1234570	8' EdgeCore FT-X Class 2 LE SRL
6274210	8' EdgeCore FT-X Class 2 LE SRL
6274226	8' EdgeCore FT-X Class 2 LE SRL
1234571	8' EdgeCore FT-X Class 2 LE SRL
6274224	8' EdgeCore FT-X Class 2 LE SRL
6274190	8' EdgeCore FT-X Class 2 LE SRL
1234568	8' EdgeCore FT-X Class 2 LE SRL
6274222	8' EdgeCore FT-X Class 2 LE SRL
6274236	8' EdgeCore FT-X Class 2 LE SRL
1234567	8' EdgeCore FT-X Class 2 LE SRL
6274215	8' EdgeCore FT-X Class 2 LE SRL
6274221	8' EdgeCore FT-X Class 2 LE SRL
6274244	8' EdgeCore FT-X Class 2 LE SRL
6274198	8' EdgeCore FT-X Class 2 LE SRL
6274215	8' EdgeCore FT-X Class 2 LE SRL
6274244	8' EdgeCore FT-X Class 2 LE SRL
6274198	8' EdgeCore FT-X Class 2 LE SRL
6274213	8' EdgeCore FT-X Class 2 LE SRL

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
	6274244	8' EdgeCore FT-X Class 2 LE SRL					
	6274198	8' EdgeCore FT-X Class 2 LE SRL					
	6274213	8' EdgeCore FT-X Class 2 LE SRL					
	6274229	8' EdgeCore FT-X Class 2 LE SRL					
	6274192	8' EdgeCore FT-X Class 2 LE SRL					
	6274214	8' EdgeCore FT-X Class 2 LE SRL					
	6274231	8' EdgeCore FT-X Class 2 LE SRL					
	6274202	8' EdgeCore FT-X Class 2 LE SRL					
	6274194	8' EdgeCore FT-X Class 2 LE SRL					
	6274242	8' EdgeCore FT-X Class 2 LE SRL					
	1234569	8' EdgeCore FT-X Class 2 LE SRL					
	6274205	8' EdgeCore FT-X Class 2 LE SRL					
	S1	8' EdgeCore FT-X Class 2 LE SRL					
	S2	8' EdgeCore FT-X Class 2 LE SRL					
	S3	8' EdgeCore FT-X Class 2 LE SRL					

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>			<b>Part No. Revision</b>	A (Both Respectively)		
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515			<b>Date Complete</b>	2/21/2022		
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail
ANSI Z359.14-2021 4.2.1	Static Strength ≥ 3600 Lbf for ≥ 60 Seconds	3631.3 Lbf	Pass
	Static Strength ≥ 3600 Lbf for ≥ 60 Seconds	3619.3 Lbf	Pass
	Static Strength ≥ 3600 Lbf for ≥ 60 Seconds	3623.2 Lbf	Pass
ANSI Z359.14-2021 4.6.1	Static Strength, Dual Configuration ≥ 3600 Lbf for ≥ 60 Seconds	3624.6 Lbf	Pass
	Static Strength, Dual Configuration ≥ 3600 Lbf for ≥ 60 Seconds	3627.9 Lbf	Pass
	Static Strength, Dual Configuration ≥ 3600 Lbf for ≥ 60 Seconds	3625.4 Lbf	Pass
ANSI Z359.14-2021 4.2.3	Locking Strength ≥ 1800 Lbf for ≥ 60 Seconds	1834.4 Lbf	Pass
	Locking Strength ≥ 1800 Lbf for ≥ 60 Seconds	1824.4 Lbf	Pass
	Locking Strength ≥ 1800 Lbf for ≥ 60 Seconds	1830.3 Lbf	Pass
ANSI Z359.14-2021 4.3.2	Dynamic Performance, 72" Freefall ≤ 1800 Lbf Max Arrest Force	1079.2 Lbf	Pass
	Visual Indicator	Clear Evidence of Impact	Pass
ANSI Z359.14-2021 4.3.2	Dynamic Performance, 72" Freefall ≤ 1800 Lbf Max Arrest Force	1193.1 Lbf	Pass
	Visual Indicator	Clear Evidence of Impact	Pass
ANSI Z359.14-2021 4.3.2	Dynamic Performance, 72" Freefall ≤ 1800 Lbf Max Arrest Force	1377.8 Lbf	Pass
	Visual Indicator	Clear Evidence of Impact	Pass
ANSI Z359.14-2021 4.6.2	Dynamic Performance, Dual Configuration ≤ 1800 Lbf Max Arrest Force	1676.4 Lbf	Pass
	Visual Indicator	Clear Evidence of Impact	Pass
ANSI Z359.14-2021 4.6.2	Dynamic Performance, Dual Configuration ≤ 1800 Lbf Max Arrest Force	1333.1 Lbf	Pass
	Visual Indicator	Clear Evidence of Impact	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>			<b>Part No. Revision</b>	A (Both Respectively)		
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515			<b>Date Complete</b>	2/21/2022		
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
ANSI Z359.14-2021 4.6.2	Dynamic Performance, Dual Configuration	≤ 1800 Lbf Max Arrest Force	1484.1 Lbf	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.3 (Perpendicular)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1073.4 Lbf	Pass			
	Avg Arrest Force	≤ 1350 Lbf Avg Arrest Force	762.3 Lbf	Pass			
	Arrest Distance	Not Applicable	122.4"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	707.5 Lbf	Pass			
ANSI Z359.14-2021 4.3.3 (Perpendicular)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1146.3 Lbf	Pass			
	Avg Arrest Force	≤ 1350 Lbf Avg Arrest Force	761.4 Lbf	Pass			
	Arrest Distance	Not Applicable	121.6"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	698.9 Lbf	Pass			
ANSI Z359.14-2021 4.3.3 (Perpendicular)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1155.5 Lbf	Pass			
	Avg Arrest Force	≤ 1350 Lbf Avg Arrest Force	803.6 Lbf	Pass			
	Arrest Distance	Not Applicable	117.8"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	703.2 Lbf	Pass			
ANSI Z359.14-2021 4.3.3 (Lateral Offset)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1226.2 Lbf	Pass			
	Avg Arrest Force	≤ 1350 Lbf Avg Arrest Force	747.5 Lbf	Pass			
	Arrest Distance	Not Applicable	132.3"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	690.4 Lbf	Pass			

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>			<b>Part No. Revision</b>	A (Both Respectively)		
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515			<b>Date Complete</b>	2/21/2022		
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
ANSI Z359.14-2021 4.3.3 (Lateral Offset)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1087.8 Lbf	Pass			
	Avg Arrest Force	≤ 1350 Lbf Avg Arrest Force	788.9 Lbf	Pass			
	Arrest Distance	Not Applicable	136.2"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	695.1 Lbf	Pass			
ANSI Z359.14-2021 4.3.3 (Lateral Offset)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1091.1 Lbf	Pass			
	Avg Arrest Force	≤ 1350 Lbf Avg Arrest Force	772.4 Lbf	Pass			
	Arrest Distance	Not Applicable	138.9"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	699.6 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.8 (Perpendicular, Hot)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1038.9 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	743.7 Lbf	Pass			
	Arrest Distance	Not Applicable	126.6"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	697.1 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.8 (Perpendicular, Hot)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1146.8 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	714.5 Lbf	Pass			
	Arrest Distance	Not Applicable	130.2"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	698.5 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.8 (Perpendicular, Hot)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1125.7 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	711.8 Lbf	Pass			
	Arrest Distance	Not Applicable	131.3"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	699.7 Lbf	Pass			

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>			<b>Part No. Revision</b>	A (Both Respectively)		
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515			<b>Date Complete</b>	2/21/2022		
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
ANSI Z359.14-2021 4.3.3.8 (Lateral Offset, Hot)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1059.9 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	730.4 Lbf	Pass			
	Arrest Distance	Not Applicable	132.0"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	702.3 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.8 (Lateral Offset, Hot)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1118.6 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	751.4 Lbf	Pass			
	Arrest Distance	Not Applicable	140.3"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	692.1 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.8 (Lateral Offset, Hot)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1009.8 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	692.4 Lbf	Pass			
	Arrest Distance	Not Applicable	125.4"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	693.3 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.9 (Perpendicular, Cold)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1174.6 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	830.5 Lbf	Pass			
	Arrest Distance	Not Applicable	96.7"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	693.4 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.9 (Perpendicular, Cold)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1291.8 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	852.8 Lbf	Pass			
	Arrest Distance	Not Applicable	110.2"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	698.6 Lbf	Pass			



### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>			<b>Part No. Revision</b>	A (Both Respectively)		
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515			<b>Date Complete</b>	2/21/2022		
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
ANSI Z359.14-2021 4.3.3.9 (Perpendicular, Cold)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1216.0 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	866.4 Lbf	Pass			
	Arrest Distance	Not Applicable	113.5"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	705.1 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.9 (Lateral Offset, Cold)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1350.0 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	859.5 Lbf	Pass			
	Arrest Distance	Not Applicable	126.8"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	698.1 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.9 (Lateral Offset, Cold)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1247.2 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	847.7 Lbf	Pass			
	Arrest Distance	Not Applicable	129.4"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	696.1 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.9 (Lateral Offset, Cold)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1191.3 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	840.8 Lbf	Pass			
	Arrest Distance	Not Applicable	126.2"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	690.6 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.10 (Perpendicular, Wet)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1148.1 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	759.0 Lbf	Pass			
	Arrest Distance	Not Applicable	125.4"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	759.4 Lbf	Pass			
ANSI Z359.14-2021	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1082.6 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	760.3 Lbf	Pass			



This laboratory is accredited with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC Communiqué dated January 2009). FallTech Testing Laboratory allows for a +/- 5% tolerance on dynamic and static strength test results.

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
ANSI Z359.14-2021 4.3.3.10 (Perpendicular, Wet)	Arrest Distance	Not Applicable	120.8"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	694.0 Lbf	Pass			

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>			<b>Part No. Revision</b>	A (Both Respectively)		
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515			<b>Date Complete</b>	2/21/2022		
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
ANSI Z359.14-2021 4.3.3.10 (Perpendicular, Wet)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1140.4 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	715.7 Lbf	Pass			
	Arrest Distance	Not Applicable	122.2"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	694.5 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.10 (Lateral Offset, Wet)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1132.0 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	762.5 Lbf	Pass			
	Arrest Distance	Not Applicable	135.8"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	720.1 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.10 (Lateral Offset, Wet)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1126.5 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	788.6 Lbf	Pass			
	Arrest Distance	Not Applicable	138.2"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	703.9 Lbf	Pass			
ANSI Z359.14-2021 4.3.3.10 (Lateral Offset, Wet)	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1044.9 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	778.2 Lbf	Pass			
	Arrest Distance	Not Applicable	139.8"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
	Line Constituent Strength	> 675 Lbf for > 60 Seconds	701.2 Lbf	Pass			

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
ANSI Z359.14-2021 4.5.1	Retraction Tension 0% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	1.8 Lbf	Pass			
	Retraction Tension 50% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	4.2 Lbf	Pass			
	Retraction Tension 100% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	5.7 Lbf	Pass			
ANSI Z359.14-2021 4.5.1	Retraction Tension 0% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	2.1 Lbf	Pass			
	Retraction Tension 50% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	5.2 Lbf	Pass			
	Retraction Tension 100% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	4.7 Lbf	Pass			
ANSI Z359.14-2021 4.5.1	Retraction Tension 0% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	1.5 Lbf	Pass			
	Retraction Tension 50% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	2.9 Lbf	Pass			
	Retraction Tension 100% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	6.7 Lbf	Pass			
ANSI Z359.14-2021 4.5.2	Horizontal Retraction	Retract Without Stopping	No Hesitation in Retraction	Pass			
ANSI Z359.14-2021 4.5.2	Horizontal Retraction	Retract Without Stopping	No Hesitation in Retraction	Pass			
ANSI Z359.14-2021 4.5.2	Horizontal Retraction	Retract Without Stopping	No Hesitation in Retraction	Pass			
ANSI Z359.14-2021 4.3.1	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1420.9 Lbf	Pass			
	Avg Arrest Force	≤ 1350 Lbf Avg Arrest Force	852.4 Lbf	Pass			
	Arrest Distance	≤ 42"	36.6"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.1	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1238.5 Lbf	Pass			
	Avg Arrest Force	≤ 1350 Lbf Avg Arrest Force	843.3 Lbf	Pass			
	Arrest Distance	≤ 42"	37.5"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.1	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1211.3 Lbf	Pass			
	Avg Arrest Force	≤ 1350 Lbf Avg Arrest Force	900.7 Lbf	Pass			
	Arrest Distance	≤ 42"	31.8"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			

### FallTech Test Report

Test Report No.	PC-2514/PC-2515	Rpt. Date	2/28/2022	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
Part No.	<b>84108SP0 / 84108TP0</b>			Part No. Revision	A (Both Respectively)		
Part Description	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
Test Request No.	PC-2514/PC-2515			Date Complete	2/21/2022		
Test Operator(s)	Yesbet Sierra / Jay Sponholz						
ANSI Z359.14-2021 4.3.1.7	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1003.6 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	785.8 Lbf	Pass			
	Arrest Distance	≤ 42"	35.3"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.1.7	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1283.5 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	776.3 Lbf	Pass			
	Arrest Distance	≤ 42"	40.1"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.1.7	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1181.9 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	792.9 Lbf	Pass			
	Arrest Distance	≤ 42"	40.4"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.1.8	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1050.7 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	817.8 Lbf	Pass			
	Arrest Distance	≤ 42"	32.8"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.1.8	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1329.2 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	867.4 Lbf	Pass			
	Arrest Distance	≤ 42"	34.4"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.1.8	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1353.7 Lbf	Pass			
	Avg Arrest Force	≤ 1575 Lbf Avg Arrest Force	916.8 Lbf	Pass			
	Arrest Distance	≤ 42"	33.9"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>			<b>Part No. Revision</b>	A (Both Respectively)		
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515			<b>Date Complete</b>	2/21/2022		
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
ANSI Z359.14-2021 4.3.1.9	Max Arrest Force	$\leq 1800$ Lbf Max Arrest Force	1131.5 Lbf	Pass			
	Avg Arrest Force	$\leq 1575$ Lbf Avg Arrest Force	724.0 Lbf	Pass			
	Arrest Distance	$\leq 42$ "	34.4"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.1.9	Max Arrest Force	$\leq 1800$ Lbf Max Arrest Force	1229.5 Lbf	Pass			
	Avg Arrest Force	$\leq 1575$ Lbf Avg Arrest Force	906.6 Lbf	Pass			
	Arrest Distance	$\leq 42$ "	29.8"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
ANSI Z359.14-2021 4.3.1.9	Max Arrest Force	$\leq 1800$ Lbf Max Arrest Force	1278.4 Lbf	Pass			
	Avg Arrest Force	$\leq 1575$ Lbf Avg Arrest Force	779.8 Lbf	Pass			
	Arrest Distance	$\leq 42$ "	37.5"	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			

#### Conclusion

Based upon the samples provided to the Lab:  
 FallTech P/Ns 84108SP0 Rev A and 84108TP0 Rev A meets the requirements of ANSI Z359.14-2021

#### Report Signatories and Approval

<b>Lab Technical Manager</b>		<b>Date</b>	2/28/2022
------------------------------	--	-------------	-----------

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515	<b>Date Complete</b>	2/21/2022				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Static Strength Test, SRL		
<b>Test Method</b>	ANSI Z359.14-2021 4.2.1		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.2.1		
<b>Test Procedure</b>	TI-239		
<b>Conditioning Requirements</b>	Not Applicable	<b>Actual Conditions</b>	Not Applicable
<b>Time Removed from Conditioning</b>	Not Applicable	<b>Time Tested</b>	Not Applicable
<b>Test Environment</b>	70.7°F / 41.9% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/15/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	323832	4/15/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274239	Static Strength	≥ 3600 Lbf for ≥ 60 Seconds	3631.3 Lbf	Pass
6274196	Static Strength	≥ 3600 Lbf for ≥ 60 Seconds	3619.3 Lbf	Pass
6274208	Static Strength	≥ 3600 Lbf for ≥ 60 Seconds	3623.2 Lbf	Pass

#### Test Information

<b>Description of Test</b>	Static Strength Test, SRL-P Dual Configuration		
<b>Test Method</b>	ANSI Z359.14-2021 4.6.1		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.6.1		
<b>Test Procedure</b>	TI-257		
<b>Conditioning Requirements</b>	Not Applicable	<b>Actual Conditions</b>	Not Applicable
<b>Time Removed from Conditioning</b>	Not Applicable	<b>Time Tested</b>	Not Applicable
<b>Test Environment</b>	70.6°F / 45.0% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/15/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	323832	4/15/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274201	Static Strength	≥ 3600 Lbf for ≥ 60 Seconds	3624.6 Lbf	Pass
6274217	Static Strength	≥ 3600 Lbf for ≥ 60 Seconds	3627.9 Lbf	Pass
6274189	Static Strength	≥ 3600 Lbf for ≥ 60 Seconds	3625.4 Lbf	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515	<b>Date Complete</b>	2/21/2022				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Locking Strength Test, SRL		
<b>Test Method</b>	ANSI Z359.14-2021 4.2.3		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.2.3		
<b>Test Procedure</b>	TI-240		
<b>Conditioning Requirements</b>	Not Applicable	<b>Actual Conditions</b>	Not Applicable
<b>Time Removed from Conditioning</b>	Not Applicable	<b>Time Tested</b>	Not Applicable
<b>Test Environment</b>	69.9°F / 41.0% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/16/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	323832	4/15/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274228	Locking Strength	≥ 1800 Lbf for ≥ 60 Seconds	1884.4 Lbf	Pass
6274203	Locking Strength	≥ 1800 Lbf for ≥ 60 Seconds	1824.4 Lbf	Pass
6274219	Locking Strength	≥ 1800 Lbf for ≥ 60 Seconds	1830.3 Lbf	Pass

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRL-P, 72" Freefall		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.2		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.2		
<b>Test Procedure</b>	TI-241		
<b>Conditioning Requirements</b>	Not Applicable	<b>Actual Conditions</b>	Not Applicable
<b>Time Removed from Conditioning</b>	Not Applicable	<b>Time Tested</b>	Not Applicable
<b>Test Environment</b>	74.0°F / 35.5% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/16/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274235	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1079.2 Lbf	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass



### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
6274204	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1193.1 Lbf	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			
6274188	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1377.8 Lbf	Pass			
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass			

### FallTech Test Report

Test Report No.	PC-2514/PC-2515	Rpt. Date	2/28/2022	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
Part No.	84108SP0 / 84108TP0		Part No. Revision	A (Both Respectively)			
Part Description	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
Test Request No.	PC-2514/PC-2515	Date Complete	2/21/2022				
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

#### Test Information

Description of Test	Dynamic Performance Test, SRL-P, Dual-configuration		
Test Method	ANSI Z359.14-2021 4.6.2		
Acceptance Criteria	ANSI Z359.14-2021 3.6.2		
Test Procedure	TI-260		
Conditioning Requirements	Not Applicable	Actual Conditions	Not Applicable
Time Removed from Conditioning	Not Applicable	Time Tested	Not Applicable
Test Environment	74.1°F / 35.4% RH		
Test By	Yesbet Sierra, Jay Sponholz	Test Date	2/16/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274195	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1676.4 Lbf	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
6274216	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1333.1 Lbf	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
6274218	Max Arrest Force	≤ 1800 Lbf Max Arrest Force	1484.1 Lbf	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass

### FallTech Test Report

Test Report No.	PC-2514/PC-2515	Rpt. Date	2/28/2022	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
Part No.	84108SP0 / 84108TP0		Part No. Revision	A (Both Respectively)			
Part Description	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
Test Request No.	PC-2514/PC-2515	Date Complete	2/21/2022				
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

#### Test Information

Description of Test	Dynamic Performance Test, SRD Class 2 (Perpendicular, Ambient)		
Test Method	ANSI Z359.14-2021 4.3.3		
Acceptance Criteria	ANSI Z359.14-2021 3.3.3		
Test Procedure	TI-247		
Conditioning Requirements	Not Applicable	Actual Conditions	Not Applicable
Time Removed from Conditioning	Not Applicable	Time Tested	Not Applicable
Test Environment	75.9°F / 30.5% RH		
Test By	Yesbet Sierra, Jay Sponholz	Test Date	2/17/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274233	Max Arrest Force	≤ 1800 Lbf	1073.4 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	762.3 Lbf	Pass
	Arrest Distance	Not Applicable	122.4"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	707.5 Lbf	Pass
6274233	Max Arrest Force	≤ 1800 Lbf	1146.3 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	761.4 Lbf	Pass
	Arrest Distance	Not Applicable	121.6"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	698.9 Lbf	Pass
6274207	Max Arrest Force	≤ 1800 Lbf	1155.5 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	803.6 Lbf	Pass
	Arrest Distance	Not Applicable	117.8"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	703.2 Lbf	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRD Class 2 (Lateral Offset, Ambient)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.3		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.3		
<b>Test Procedure</b>	TI-248		
<b>Conditioning Requirements</b>	Not Applicable	<b>Actual Conditions</b>	Not Applicable
<b>Time Removed from Conditioning</b>	Not Applicable	<b>Time Tested</b>	Not Applicable
<b>Test Environment</b>	76.0°F / 28.5% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/17/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274240	Max Arrest Force	≤ 1800 Lbf	1226.2 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	747.5 Lbf	Pass
	Arrest Distance	Not Applicable	132.3"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	690.4 Lbf	Pass
6274191	Max Arrest Force	≤ 1800 Lbf	1087.8 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	788.9 Lbf	Pass
	Arrest Distance	Not Applicable	136.2"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	695.1 Lbf	Pass
6274220	Max Arrest Force	≤ 1800 Lbf	1091.1 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	772.4 Lbf	Pass
	Arrest Distance	Not Applicable	138.9"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	699.6 Lbf	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515	<b>Date Complete</b>	2/21/2022				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRD Class 2 (Perpendicular, Hot)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.3.8		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.3		
<b>Test Procedure</b>	TI-249		
<b>Conditioning Requirements</b>	Condition at 130°F; Min RH of 85% for 2 Hours, +30/-0 Minutes	<b>Actual Conditions</b>	Conditioned at 130°F; Min RH of 85% for 2 Hours, 12 Minutes
<b>Time Removed from Conditioning</b>	11:12 AM - 1:24 PM	<b>Time Tested</b>	11:12 AM - 1:24 PM
<b>Test Environment</b>	71.5°F / 38.4% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/17/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021
Hot Chamber	26.4 Cubic Ft	CE59E00	4/15/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274230	Max Arrest Force	≤ 1800 Lbf	1038.9 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	743.7 Lbf	Pass
	Arrest Distance	Not Applicable	126.6"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	697.1 Lbf	Pass
6274227	Max Arrest Force	≤ 1800 Lbf	1146.8 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	714.5 Lbf	Pass
	Arrest Distance	Not Applicable	130.2"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	698.5 Lbf	Pass
6274212	Max Arrest Force	≤ 1800 Lbf	1125.7 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	711.8 Lbf	Pass
	Arrest Distance	Not Applicable	131.3"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	699.7 Lbf	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRD Class 2 (Lateral Offset, Hot)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.3.8		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.3		
<b>Test Procedure</b>	TI-250		
<b>Conditioning Requirements</b>	Condition at 130°F; Min RH of 85% for 2 Hours, +30/-0 Minutes	<b>Actual Conditions</b>	Conditioned at 130°F; Min RH of 85% for 2 Hours 10 Minutes
<b>Time Removed from Conditioning</b>	8:20 AM - 10:30 AM	<b>Time Tested</b>	8:20 AM - 10:30 AM
<b>Test Environment</b>	68.9°F / 33.1% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/18/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021
Hot Chamber	26.4 Cubic Ft	CE59E00	4/15/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274230	Max Arrest Force	≤ 1800 Lbf	1059.9 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	730.4 Lbf	Pass
	Arrest Distance	Not Applicable	132.0"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	702.3 Lbf	Pass
6274227	Max Arrest Force	≤ 1800 Lbf	1118.6 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	751.4 Lbf	Pass
	Arrest Distance	Not Applicable	140.3"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	692.1 Lbf	Pass
6274212	Max Arrest Force	≤ 1800 Lbf	1009.8 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	692.4 Lbf	Pass
	Arrest Distance	Not Applicable	125.4"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	693.3 Lbf	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515	<b>Date Complete</b>	2/21/2022				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRD Class 2 (Perpendicular, Cold)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.3.9		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.3		
<b>Test Procedure</b>	TI-251		
<b>Conditioning Requirements</b>	Condition at -40°C for 2 Hours, +30/-0 Minutes	<b>Actual Conditions</b>	Conditioned at -40°C for 2 Hours 7 Minutes
<b>Time Removed from Conditioning</b>	9:40 AM - 11:47 AM	<b>Time Tested</b>	9:41 AM - 11:48 AM
<b>Test Environment</b>	73.0°F / 36.7% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/17/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021
Cold Chamber	5 Cubic Ft	12732	7/23/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
1234570	Max Arrest Force	≤ 1800 Lbf	1174.6 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	830.5 Lbf	Pass
	Arrest Distance	Not Applicable	96.7"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	693.4 Lbf	Pass
6274210	Max Arrest Force	≤ 1800 Lbf	1291.8 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	852.8 Lbf	Pass
	Arrest Distance	Not Applicable	110.2"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	698.6 Lbf	Pass
6274226	Max Arrest Force	≤ 1800 Lbf	1216.0 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	866.4 Lbf	Pass
	Arrest Distance	Not Applicable	113.5"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	705.1 Lbf	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515	<b>Date Complete</b>	2/21/2022				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRD Class 2 (Lateral Offset, Cold)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.3.9		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.3		
<b>Test Procedure</b>	TI-252		
<b>Conditioning Requirements</b>	Condition at -40°C for 2 Hours, +30/-0 Minutes	<b>Actual Conditions</b>	Conditioned at -40°C for 2 Hours 23 Minutes
<b>Time Removed from Conditioning</b>	9:20 AM - 11:43 AM	<b>Time Tested</b>	9:21 AM - 11:44 AM
<b>Test Environment</b>	73.4°F / 29.4% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/18/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021
Cold Chamber	5 Cubic Ft	12732	7/23/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
1234571	Max Arrest Force	≤ 1800 Lbf	1350.0 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	859.5 Lbf	Pass
	Arrest Distance	Not Applicable	126.8"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	698.1 Lbf	Pass
6274224	Max Arrest Force	≤ 1800 Lbf	1247.2 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	847.7 Lbf	Pass
	Arrest Distance	Not Applicable	129.4"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	696.1 Lbf	Pass
6274190	Max Arrest Force	≤ 1800 Lbf	1191.3 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	840.8 Lbf	Pass
	Arrest Distance	Not Applicable	126.2"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	690.6 Lbf	Pass



### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515	<b>Date Complete</b>	2/21/2022				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRD Class 2 (Perpendicular, Wet)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.3.10		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.3		
<b>Test Procedure</b>	TI-253		
<b>Conditioning Requirements</b>	Immerse in Water for 3 Hours +30 / -0 Minutes	<b>Actual Conditions</b>	Immersed in Water for 3 Hours and 13 Minutes
<b>Time Removed from Conditioning</b>	10:20 AM - 1:33 PM	<b>Time Tested</b>	10:21 AM - 1:34 PM
<b>Test Environment</b>	75.4°F / 30.4% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/17/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021
Wet Chamber	94.6 Ltr	N/A	N/A

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
1234568	Max Arrest Force	≤ 1800 Lbf	1148.1 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	759.0 Lbf	Pass
	Arrest Distance	Not Applicable	125.4"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	759.4 Lbf	Pass
6274222	Max Arrest Force	≤ 1800 Lbf	1082.6 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	760.3 Lbf	Pass
	Arrest Distance	Not Applicable	120.8"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	694.0 Lbf	Pass
6274236	Max Arrest Force	≤ 1800 Lbf	1140.4 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	715.7 Lbf	Pass
	Arrest Distance	Not Applicable	122.2"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	694.5 Lbf	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRD Class 2 (Lateral Offset, Wet)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.3.10		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.3		
<b>Test Procedure</b>	TI-254		
<b>Conditioning Requirements</b>	Immerse in Water for 3 Hours +30 / -0 Minutes	<b>Actual Conditions</b>	Immersed in Water for 3 Hours and 9 Minutes
<b>Time Removed from Conditioning</b>	10:30 AM - 1:39 PM	<b>Time Tested</b>	10:31 AM - 1:40 PM
<b>Test Environment</b>	75.5°F / 26.2% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/18/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021
Wet Chamber	94.6 Ltr	N/A	N/A

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
1234567	Max Arrest Force	≤ 1800 Lbf	1132.0 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	762.5 Lbf	Pass
	Arrest Distance	Not Applicable	135.8"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	720.1 Lbf	Pass
6274215	Max Arrest Force	≤ 1800 Lbf	1126.5 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	788.6 Lbf	Pass
	Arrest Distance	Not Applicable	138.2"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	703.9 Lbf	Pass
6274221	Max Arrest Force	≤ 1800 Lbf	1044.9 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	778.2 Lbf	Pass
	Arrest Distance	Not Applicable	139.8"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
	Line Strength	> 675 Lbf for 1 Minute	701.2 Lbf	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Retraction Tension, SRL		
<b>Test Method</b>	ANSI Z359.14-2021 4.5.1		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.5		
<b>Test Procedure</b>	TI-246		
<b>Conditioning Requirements</b>	Not Applicable	<b>Actual Conditions</b>	Not Applicable
<b>Time Removed from Conditioning</b>	Not Applicable	<b>Time Tested</b>	Not Applicable
<b>Test Environment</b>	71.9°F / 36.5% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/16/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Measuring Tape	35 Ft	ALE-35814	4/24/2021
Force Gauge	44 Lbs	2019140351	11/11/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274244	Retraction Tension 0% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	1.8 Lbf	Pass
	Retraction Tension 50% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	4.2 Lbf	Pass
	Retraction Tension 100% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	5.7 Lbf	Pass
6274198	Retraction Tension 0% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	2.1 Lbf	Pass
	Retraction Tension 50% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	5.2 Lbf	Pass
	Retraction Tension 100% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	4.7 Lbf	Pass
6274213	Retraction Tension 0% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	1.5 Lbf	Pass
	Retraction Tension 50% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	2.9 Lbf	Pass
	Retraction Tension 100% Extracted	1.25 Lbf - 25 Lbf ≤ 48" Extended	6.7 Lbf	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	84108SP0 / 84108TP0		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515	<b>Date Complete</b>	2/21/2022				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Horizontal Retraction Tension, SRL		
<b>Test Method</b>	ANSI Z359.14-2021 4.5.2		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.5		
<b>Test Procedure</b>	TI-246		
<b>Conditioning</b>	Not Applicable	<b>Actual Conditions</b>	Not Applicable
<b>Time Removed from Conditioning</b>	Not Applicable	<b>Time Tested</b>	Not Applicable
<b>Test Environment</b>	71.9°F / 36.5% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/16/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Measuring Tape	35 Ft	ALE-35814	4/24/2021
Force Gauge	44 Lbs	2019140351	11/11/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274244	Horizontal Retraction	Retract Without Stopping	No Hesitation in Retraction	Pass
6274198	Horizontal Retraction	Retract Without Stopping	No Hesitation in Retraction	Pass
6274213	Horizontal Retraction	Retract Without Stopping	No Hesitation in Retraction	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRL Attached to Test Weight (Ambient)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.1		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.1		
<b>Test Procedure</b>	TI-261		
<b>Conditioning Requirements</b>	Not Applicable	<b>Actual Conditions</b>	Not Applicable
<b>Time Removed from Conditioning</b>	Not Applicable	<b>Time Tested</b>	Not Applicable
<b>Test Environment</b>	68.0°F / 37.7% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/16/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274244	Max Arrest Force	≤ 1800 Lbf	1420.9 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	852.4 Lbf	Pass
	Arrest Distance	≤ 42"	36.6"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
6274198	Max Arrest Force	≤ 1800 Lbf	1238.5 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	843.3 Lbf	Pass
	Arrest Distance	≤ 42"	37.5"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
6274213	Max Arrest Force	≤ 1800 Lbf	1211.3 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	900.7 Lbf	Pass
	Arrest Distance	≤ 42"	31.8"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515	<b>Date Complete</b>	2/21/2022				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRL Attached to Test Weight (Hot)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.1.7		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.1		
<b>Test Procedure</b>	TI-262		
<b>Conditioning Requirements</b>	Condition at 130°F; Min RH of 85% for 2 Hours, +30/-0 Minutes	<b>Actual Conditions</b>	Conditioned at 130°F; Min RH of 85% for 2 Hours 11 Minutes
<b>Time Removed from Conditioning</b>	8:00 AM - 10:11 AM	<b>Time Tested</b>	8:01 AM - 10:12 AM
<b>Test Environment</b>	68.2°F / 37.8% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/16/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021
Hot Chamber	26.4 Cubic Ft	CE59E00	4/15/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274229	Max Arrest Force	≤ 1800 Lbf	1003.6 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	785.8 Lbf	Pass
	Arrest Distance	≤ 42"	35.3"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
6274192	Max Arrest Force	≤ 1800 Lbf	1283.5 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	776.3 Lbf	Pass
	Arrest Distance	≤ 42"	40.1"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
6274214	Max Arrest Force	≤ 1800 Lbf	1181.9 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	792.9 Lbf	Pass
	Arrest Distance	≤ 42"	40.4"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass

### FallTech Test Report

Test Report No.	PC-2514/PC-2515	Rpt. Date	2/28/2022	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
Part No.	84108SP0 / 84108TP0		Part No. Revision	A (Both Respectively)			
Part Description	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
Test Request No.	PC-2514/PC-2515	Date Complete	2/21/2022				
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

#### Test Information

Description of Test	Dynamic Performance Test, SRL Attached to Test Weight (Cold)		
Test Method	ANSI Z359.14-2021 4.3.1.8		
Acceptance Criteria	ANSI Z359.14-2021 3.3.1		
Test Procedure	TI-263		
Conditioning Requirements	Condition at -40°C for 2 Hours, +30/-0 Minutes	Actual Conditions	Conditioned at -40°C for 2 Hours 19 Minutes
Time Removed from Conditioning	8:20 AM - 10:39 AM	Time Tested	8:21 AM - 10:40 AM
Test Environment	69.5°F / 36.8% RH		
Test By	Yesbet Sierra, Jay Sponholz	Test Date	2/16/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021
Cold Chamber	5 Cubic Ft	12732	7/23/2021

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274231	Max Arrest Force	≤ 1800 Lbf	1050.7 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	817.8 Lbf	Pass
	Arrest Distance	≤ 42"	32.8"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
6274202	Max Arrest Force	≤ 1800 Lbf	1329.2 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	867.4 Lbf	Pass
	Arrest Distance	≤ 42"	34.4"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
6274194	Max Arrest Force	≤ 1800 Lbf	1353.7 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	916.8 Lbf	Pass
	Arrest Distance	≤ 42"	33.9"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	<b>84108SP0 / 84108TP0</b>		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515		<b>Date Complete</b>	2/21/2022			
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

#### Test Information

<b>Description of Test</b>	Dynamic Performance Test, SRL Attached to Test Weight (Wet)		
<b>Test Method</b>	ANSI Z359.14-2021 4.3.1.9		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.3.1		
<b>Test Procedure</b>	TI-264		
<b>Conditioning Requirements</b>	Immerse in Water for 3 Hours +30 / -0 Minutes	<b>Actual Conditions</b>	Immersed in Water for 3 Hours 5 Minutes
<b>Time Removed from Conditioning</b>	11:00 AM - 2:05 PM	<b>Time Tested</b>	11:01 AM - 2:06 PM
<b>Test Environment</b>	70.1°F / 35.7% RH		
<b>Test By</b>	Yesbet Sierra, Jay Sponholz	<b>Test Date</b>	2/16/2022

#### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	342183	4/15/2021
Test Weight	300 Lbs	TW300	4/15/2021
Test Weight	10 Lbs	TW10	4/15/2021
Altimeter	60 Ft	ALE-87283	4/27/2021
Wet Chamber	94.6 Ltr	N/A	N/A

#### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
6274242	Max Arrest Force	≤ 1800 Lbf	1131.5 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	724.0 Lbf	Pass
	Arrest Distance	≤ 42"	34.4"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
1234569	Max Arrest Force	≤ 1800 Lbf	1229.5 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	906.6 Lbf	Pass
	Arrest Distance	≤ 42"	29.8"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass
6274205	Max Arrest Force	≤ 1800 Lbf	1278.4 Lbf	Pass
	Avg Arrest Force	≤ 1350 Lbf	779.8 Lbf	Pass
	Arrest Distance	≤ 42"	37.5"	Pass
	Visual Indicator	Clear Evidence of Impact	Clear Evidence	Pass

#### Test Information

<b>Description of Test</b>	Static Strength Test, SRL-P Connector		
<b>Test Method</b>	ANSI Z359.14-2021 4.2.2		
<b>Acceptance Criteria</b>	ANSI Z359.14-2021 3.2.2		
<b>Test Procedure</b>	TI-256		
<b>Conditioning Requirements</b>	Not Applicable	<b>Actual Conditions</b>	Not Applicable
<b>Time Removed from Conditioning</b>	Not Applicable	<b>Time Tested</b>	Not Applicable
<b>Test Environment</b>	66.8°F / 48.0% RH		



### FallTech Test Report

<b>Test Report No.</b>	PC-2514/PC-2515	<b>Rpt. Date</b>	2/28/2022	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.14-2021: 4.2.1, 4.2.2, 4.2.3, 4.3.2, 4.3.3, 4.5.1, 4.5.2, 4.3.1, 4.6.1, 4.6.2				
<b>Part No.</b>	84108SP0 / 84108TP0		<b>Part No. Revision</b>	A (Both Respectively)			
<b>Part Description</b>	8' EdgeCore FT-X Class 2 LE SRL, Single-leg with Steel Mini Rebar Hook 8' EdgeCore FT-X Class 2 LE SRL, Twin-leg with Steel Mini Rebar Hook						
<b>Test Request No.</b>	PC-2514/PC-2515	<b>Date Complete</b>	2/21/2022				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						
<b>Test By</b>	Oscar Jaramillo	<b>Test Date</b>	2/21/2022				

### Equipment Used

Equipment Used	Size/Type	Control Number	Calibration Date
Load Cell	10,000 Lbs	323832	4/15/2021

### Test Results

Sample ID	Characteristic	Criteria	Test Data	Pass/Fail
S1	Static Strength	≥ 3600 Lbf for ≥ 60 Seconds	3631.6 Lbf	Pass
S2	Static Strength	≥ 3600 Lbf for ≥ 60 Seconds	3633.0 Lbf	Pass
S3	Static Strength	≥ 3600 Lbf for ≥ 60 Seconds	3627.1 Lbf	Pass