

## 721520LEC

FT-R™ Class 2 Leading Edge SRL with 20' Galvanized Steel Cable, 420 lb max.

Calculate Your  
Fall Clearance



### Features :

- 20% lighter than typical 20' Cable Class 2 Leading Edge SRLs
- 7/32" galvanized steel cable lifeline with swivel snap hook
- Innovative energy absorber design provides more consistent performance in all environmental conditions and features full fall clearance diagrams and charts inside the Viewpack®
- Improved internal mechanism design minimizes unintentional lockups to keep workers moving freely and productively
- Swiveling anchor and leg-end connectors plus an integrated carrying handle simplify installation and transportation
- Industry first UV-resistant and scratch resistant label keep warnings legible and units in service
- Includes steel anchorage carabiner with 3/4" gate opening
- Complies with ANSI Z359.14-2021 Class 2 SRL. [Learn more and download White Paper](#)



Material Specifications	
<b>Cable</b>	7/32" galvanized steel; 3,600 lb min. static strength
<b>Energy Absorber</b>	Polyester tear-away
<b>Lifeline Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
<b>Static Strength</b>	3,600 lb min.
<b>ANSI SRL Class/Type</b>	Class 2 SRL
<b>Avg. Arrest Force</b>	1,350 lb max.
<b>Max. Arrest Force</b>	1,800 lb
<b>Max. Arrest Distance</b>	42"
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 420 lb max.

Compliant With:	
<b>CSA</b>	Z259.2.2-2017(R2022)
<b>OSHA</b>	1926.502 and 1910.66
<b>ANSI</b>	Z359.14-2021

### Sizes & Part Numbers

721520LEC - 20'	721530LEC - 30'	721560LEC - 60'
-----------------	-----------------	-----------------

