


SPREADER BEAMS

Telescoping Adjustable Spread - Large Capacity Shackle End

- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Painted safety yellow for increased visibility.
- ALL Spreader Beams shipped with proof load certification paperwork.
- Durable construction ideally suited to jobsite or warehouse use.
- Made in U.S.A.
- Custom designs available - call for engineering.

- ALL lifting equipment individually proof loaded per OSHA requirements.
- Minimum horizontal top rigging angle of 45°
- Ideally suited for adding stability to critical lifts.
- Beam only. Shackles supplied by others.

 Prop 65 – See Page 112



SHOWN WITH OPTIONAL TOP RIGGING & SHACKLES

TELESCOPING ADJUSTABLE LARGE CAPACITY SHACKLE END SPREADER BEAMS							
Working Load Limit in Pounds*	Shackle Size	Model Number Headroom (in) Weight (lbs)	Outside Spread (L) in Feet*				
			Min Max 5'6" - 7'	Min Max 7 - 10	Min Max 10 - 14	Min Max 14 - 20	Min Max 21 - 30
40,000	1-1/2" Top 1-1/2" Bottom	Part Number	20127	20126	20125	20124	24406
		HR =	7.6	7.6	7.6	7.6	7.6
60,000	1-3/4" Top 1-3/4" Bottom	Part Number	20132	20131	20130	20129	24407
		HR =	7.1	7.1	7.1	7.1	7.1
80,000	2" Top 2" Bottom	Part Number	20137	20136	20135	20134	24413
		HR =	9.3	9.3	9.3	9.3	9.3
100,000	2" Top 2" Bottom	Part Number	20142	20141	20140	20139	24408
		HR =	9.3	9.3	9.3	9.3	9.3
150,000	2-1/2" Top 2-1/2" Bottom	Part Number	N/A	24412	24411	24410	24409
		HR =		13.9	13.9	13.9	13.9
		LBS =		340	410	560	760
				395	490	660	890
				575	700	950	1,250
					700	950	1,250
						1310	1640
							2120
							2995

OPTIONAL TOP RIGGING							
Working Load Limit in Pounds*	Part Name		Part Number	Part Number	Part Number	Part Number	Part Number
40,000	Adjustable Spreader		20127	20126	20125	20124	24406
	Wire Rope		23421	23422	23423	23424	24414
	Round Sling Bridle		23433	23434	23435	23436	24422
60,000	Adjustable Spreader		20132	20131	20130	20129	24407
	Wire Rope		23425	23426	23427	23428	24415
	Round Sling Bridle		23437	23438	23439	23440	24423
80,000	Adjustable Spreader		20137	20136	20135	20134	24413
	Wire Rope		23430	23430	23431	23432	24416
	Round Sling Bridle		23441	23442	23443	23444	24424
100,000	Adjustable Spreader		20142	20141	20140	20139	24408
	Wire Rope		23430	23430	23431	23432	24416
	Round Sling Bridle		23441	23442	23443	23444	24424
150,000	Adjustable Spreader		N/A	24412	24411	24410	24409
	Round Sling Bridle		N/A	24418	24417	24426	24425

*Minimum horizontal top rigging angle is 45° on all fixed and adjustable spreaders. M&W recommends a minimum horizontal top rigging angle of 60°. Adjustable on 6" increments.